<u>Panasonic</u>

HD Analog Digital Video Recorder CJ-HDR104 CJ-HDR108

4 CH/ 8 CH HD Analog Digital Video Recorder






Key Features

- 4 CH (CJ-HDR104) / 8 CH (CJ-HDR108) with 720p real-time recording playback and live view
- H.264 video encode
- HDMI/ VGA simultaneous video output
- Support 1 SATA HDDs up to 6TB, 2 USB
- Digital Zoom in Live & Playback
- iPhone, iPad, & Android

Standard Accessories

- Quick guide.....1 pc
- Important safety instruction......1 pc
- CD1pc

Appearance



Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.

CJ-HDR104 CJ-HDR108 Video/ Audio IF 4 CH, BNC 8 CH, BNC Video Input HDCVI 720p/ 1080p HDCVI Type NTSC/ PAL Analog Video Output 1 HDMI, 1 VGA Audio Input 1 CH, RCA Audio Output 1 CH, RCA Reuse audio input/ output CH 1 Two-way Talk Display **Output Resolution** 1920×1080, 1280×1024, 1280×720, 1024×768 Multiscreen Mode 1/41/4/8/9 Privacy Masking 4 rectangular zones (each camera) Camera title, Time, Video loss, Camera lock, Motion detection, OSD Recording Video/ Audio Format Video/ Audio Compression H.264/G.711 Main Stream 1080P (1~12/15fps)/ 720P/ 960H/ D1 (1~25/30fps) Record Rate Extra Stream CIF/ QCIF (1~25/30fps), D1 (1~12/15fps) Bit Rate 96~4096Kb/s Record Mode Manual, Schedule (Regular (Continuous), MD), Stop 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: Record Interval 10~300 se Alarm/ Event Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Trigger Events Buzzer & Screen tips Motion Detection, MD Zones: 396 (22x18), Video Loss & Video Detection Camera Blank Playback & Backup Sync Playback 1/4 1/4/9 Search Mode Time/ Date, MD & Exact search (accurate to second) Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, **Playback Functions** Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom Backup Mode USB Device/ Network Network Network Interface RJ-45 port (10/ 100M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P Network Functions Max. User Access 128 users Mobile Device iPhone, iPad, Android HDD 1 SATA port, up to 6TB Туре **External Interface** USB Interface 2 ports (1 Rear), USB2.0 RS485 Camera Interface 1 port, For PTZ Control **General Specifications** DC12V/4A Power Supply **Power Consumption** 10W (without HDD) Working Environment -10°C~+55°C / 10%~90%RH / 86~106kpa Dimension(WxDxH) Mini 1U, 325mm×255mm×55mm Weight 1.5KG (without HDD)

-Auto Reboot (once a week)

All pictures are simulated.

- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

DISTRIBUTED BY: